

# ROTOTILLER



| Ref         |  |  |  4 |  6 |  mm (in) | LPM     |  |  KG |
|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| 08.RC.0850S | 850                                                                               | 990                                                                               | 16 - 24                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 190                                                                                 |                                                                                        |
| 08.RC.1050S | 1050                                                                              | 1180                                                                              | 20 - 30                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 210                                                                                 |                                                                                        |
| 08.RC.1250S | 1250                                                                              | 1380                                                                              | 24 - 36                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 230                                                                                 |                                                                                        |
| 08.RC.1350S | 1350                                                                              | 1480                                                                              | 28 - 42                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 248                                                                                 |                                                                                        |
| 08.RC.1450S | 1450                                                                              | 1580                                                                              | 28 - 42                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 254                                                                                 |                                                                                        |
| 08.RC.1650S | 1650                                                                              | 1780                                                                              | 32 - 48                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 276                                                                                 |                                                                                        |
| 08.RC.1850S | 1850                                                                              | 1980                                                                              | 36 - 54                                                                             | 100 - 200                                                                           | min. 40                                                                                    | 180-210 | 298                                                                                 |                                                                                        |

Standard 6 curved blades per flange mounted in spiral line (normal soils) - *optional 4 blades*



EC safety guards (standard in European Community)



Adjustable side skids to determine the desired working depth

