# DECLARATION OF PERFORMANCE – NR. 065/CPR/171017

I. Unique identification code of the product-type:

**VARIOFLEX**

II. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**VARIOFLEX - Cementitious tile adhesive C2 TE**
**(The batch number is printed on the packaging)**

III. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Flexible tile adhesive for floor and wall, for internal and external use**

IV. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**COMPAKTUNA bv/srl**
**INDUSTRIEPARK ZWIJNAARDE 6**
**9052 GENT - BELGIUM**

V. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

VI. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**Systeem 3**

VII. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 12004+ A1:2012**

The **BELGIAN BUILDING RESEARCH INSTITUTE (BBRI) No. 1136** carried out the determination of the product-type, the C2-performance, on the basis of type testing on samples taken by the manufacturer under system 3

VIII. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

# DECLARATION OF PERFORMANCE – NR. 065/CPR/171017

IX. Declared performance

| Essential characteristics | Performances | Harmonized technical specification |
|---|---|---|
| **Reaction to fire** | **E** | **EN 12004+ A1:2012** |
| **Bond strength as:**<br>**- Initial tensile adhesion strength** | **≥ 1 N/mm²** | |
| **Durability for:**<br>**- Tensile adhesion strength after heat ageing**<br>**- Tensile adhesion strength after water immersion**<br>**- Tensile adhesion strength after freeze-thaw cycles** | **≥ 1 N/mm²** | |
| **Release of dangerous substances** | **See SDS** | |

X. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**P. D'HAENENS, DIRECTOR SOLUTIONS & PRODUCTS**
(name and function)

**GENT, 03/04/2023**
(place and date of issue)

**COMPAKTUNA bv/srl**
Industriepark III - Industriepark Zwijnaarde 6 - 9052 Gent - Belgium
TEL. +32 9 221 11 16 - info@compaktuna.be - www.compaktuna.be