

DECLARATION OF PERFORMANCE – NR. 058/CPR/180518

- I. Unique identification code of the product-type:

MEMBRANE LIQ

- II. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

MEMBRANE LIQ

(The batch number is printed on the packaging)

- III. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Liquid-applied water impermeable product for use beneath ceramic tiling bonded with adhesives (Type C2 according to EN 12004)

- IV. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**COMPAKTUNA bv/srl
INDUSTRIEPARK ZWIJNAARDE 6
9052 GENT - BELGIUM**

- V. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

- VI. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

- VII. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 14891:2012

The Materialprüfungsamt Nordrhein-Westfalen (MPA NRW) No. 0432 carried out the determination of the waterproofing ability of the product, on the basis of type testing under system 3 (Report 220012712-18-1)

- VIII. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

DECLARATION OF PERFORMANCE – NR. 058/CPR/180518

IX. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Initial tensile adhesion strength	≥0,5 N/mm ²	EN 14891:2012
Tensile adhesion strength after: - Heat ageing - Water immersion - Freeze-thaw cycles - Contact with lime water	≥0,5 N/mm ²	
Waterproofing	No penetration	
Crack bridging ability : - Under normal circumstances (23°C) - At low temperature (-5°C)	≥0,75 mm	
Release of dangerous substances	See MSDS	

- X. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

P. D'HAENENS, DIRECTOR SOLUTIONS & PRODUCTS
(name and function)

GENT, 04/04/2023
(place and date of issue)

