DECLARATION OF PERFORMANCE – NR. 823/CPR/220304

I. Unique identification code of the product-type:

FLEXcement® PREMIUM

II. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

FLEXcement® PREMIUM - Cementitious tile adhesive C2 TE S2
(The batch number is printed on the packaging)

III. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Flexible tile adhesive for floor and wall, for internal and external use

IV. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

COMPAKTUNA® bv/srl
INDUSTRIEPARK ZWIJNAARDE 6
9052 GENT - BELGIUM

V. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

VI. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

VII. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12004:2007+A1:2012

The notified body **centre Scientifique et Technique du Bâtiment (CSTB) (idNr 0679)** carried out the determination of the product-type, the C2-performance, on the basis of type testing on samples taken by the manufacturer under system 3

VIII. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

DECLARATION OF PERFORMANCE – NR. 823/CPR/220304

IX. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	NPD	EN 12004:2007+A1:2012
Bond strength as: -Initial tensile adhesion strength	≥ 1 N/mm²	
Durability for: -Tensile adhesion strength after heat ageing -Tensile adhesion strength after water immersion -Tensile adhesion strength after freeze-thaw cycles	≥ 1 N/mm² ≥ 1 N/mm² ≥ 1 N/mm²	
Release of dangerous substances	See MSDS	

X. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

P. D'HAENENS, DIRECTOR SOLUTIONS & PRODUCTS
(name and function)

GENT, 28/06/2023
(place and date of issue)

