

COMPAKTUNA®

PIGMENT M

Pigment for colouring  
mortar and concrete




RECOMMENDATIONS

- Perform a test in advance to determine the desired colour of the mortar. Adjust the amount of pigment to this.
- Once the pigmentation ratio has been determined, always maintain the same amount of mixing water and mixing time to avoid colour differences.



CONDITION OF APPLICATION

Operating temperature: +5 °C to +30 °C.



DIRECTIONS FOR USE

- Scatter the pigment and mix dry with the cement.
- Add the mixing water to the mortar and mix until a mortar with a homogeneous colour is obtained.

| Available in:  | 0,3 kg | 0,75 kg | 4 kg | 20 kg | 25 kg |
|----------------|--------|---------|------|-------|-------|
| Black          |        | x       | x    |       | x     |
| Red            |        | x       | x    |       | x     |
| Brown          |        | x       | x    |       | x     |
| Green          |        |         | x    |       | x     |
| Titanium white |        |         | x    |       | x     |
| Ocher yellow   | x      |         | x    | x     |       |
| Beige          |        |         | x    |       | x     |



| Mixing ratio    | Consumption                 | Packaging       |
|-----------------|-----------------------------|-----------------|
| Undiluted       | ±1% to 10% on cement weight | See table above |
| Colour          | Application temperature     |                 |
| See table above | +5 °C to +30 °C             |                 |

As the applications of our products are diverse, no single application guideline can be laid down. All product data reflect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignificant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website [www.compaktuna.be](http://www.compaktuna.be). Consult our "technical department" which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding.  
Version 10/02/2014. COMPACTUNA BV is EN ISO 9001 certified.

COMPACTUNA®  
— Quality & Innovation —



COMPACTUNA bv/srl  
Industriepark III  
Industriepark Zwijnaarde 6  
9052 Gent - Belgium  
T +32 9 221 11 16  
VAT BE0400.166.768 - R.P.R. Gent  
[info@compaktuna.be](mailto:info@compaktuna.be)  
[www.compaktuna.be](http://www.compaktuna.be)