COMPAKTUNA®

GEDROOGD KWARTSZAND

Dried colored quartz sand

DARK BROWN AND BLACK



CHARACTERISTICS

Dried quartz sand is used as jointing material with a grain size of 0.3 to 0.8 mm for patios with clay and concrete pavers.

APPLICATIONS

Joint sand

For filling joints in pavements, driveways, terraces, floors, etc. The sand effortlessly fills all gaps and cracks, and absorbs little water, allowing it to dry quickly after moistening.

Decorative sand

E.g., in aquariums and terrariums, ...

REMARKS

For fixing joints with DRIED QUARTZ SAND, we recommend SEAL-ALL® JOINT.

PACKAGING

DRIED QUARTZ SAND is available in 25kg bags. It is available in dark brown and black.

As the applications of our products are diverse, no single application guideline can be laid down. All product data reflect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignifi cant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website www.compaktuna.be. Consult our “technical department” which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding.
Version 10/02/2014. **COMPAKTUNA BV is EN ISO 9001 certified.**

COMPAKTUNA®
Quality & Innovation

A MEMBER OF HOLCIM GROUP

COMPAKTUNA bv/srl
Industriepark III
Industriepark Zwijnaarde 6
9052 Gent - Belgium
T +32 9 221 11 16
VAT BE0400.166.768 - R.P.R. Gent
info@compaktuna.be
www.compaktuna.be