COMPAKTUNA®

POLYCOLORIT®

Waterproof paint
















CHARACTERISTICS

POLYCOLORIT® is used for waterproof, weather-resistant painting of villas, houses, industrial buildings, garages, warehouses, etc. In addition to excellent workability, POLYCOLORIT® allows for a perfect finish. A clean surface free of oil and grease, dust, and loose parts is always a prerequisite for a good result.

Mixing ratio	Consumption	Packaging
Base layer: dilute with ± 33% water Coating: undiluted	Base layer: ± 0,10 L/m² Coating: ± 0,15 L/m²	4 L
Color	**Processing time**	**Operating temperature**
White	2 to 5 hours	+10 °C to +30 °C

POLYCOLORIT®

DIRECTIONS OF USE

Always apply a primer with the following composition:

- 2 parts by volume of POLYCOLORIT®
- 1 part by volume of water

Let it dry. Then, apply two topcoats with undiluted POLYCOLORIT®.

For damp areas, first, fix the water infiltration issues. For damp walls or walls with salt efflorescence (which must be removed), we recommend the following primer composition for the first coat:


- 1 part by volume of water and 1 part by volume of white cement mixed together, then add 2.5 parts by volume of POLYCOLORIT®.

The second topcoat is applied with undiluted POLYCOLORIT®. For less stable substrates (unstable joints or plastering), we can provide a special procedure using our product COMPAKTUNA®.

POLYCOLORIT® can also be applied as a dust-binding, wear-resistant colored coating for cement, concrete, cork, and other screeds primarily used for foot traffic. For this application, we recommend a primer, 2 topcoats with cement, and a finishing coat with undiluted POLYCOLORIT®.







20240806

Since the applications and uses of our products are diverse, it is not possible to establish a single application guideline. All product information refl ects the state of knowledge of our products at the time of publication. Therefore, any suggestions or recommendations regarding the use of our products are purely illustrative. Before using our products and in order to achieve the desired result, apply them to a small, inconspicuous area. In any case, do not forget to ask for the technical data sheet for our products! Visit our website www.compaktuna.be and consult our "Technical Service". This service is free of charge and available by calling our toll-free number 0800/92279. Only the Dutch version of the text is binding and exclusively applicable. Version 10/02/2014. **COMPAKTUNA bv is EN ISO 9001 certified.**

COMPAKTUNA®
Quality & Innovation

A MEMBER OF HOLCIM GROUP

COMPAKTUNA bv/srl
Industriepark III
Industriepark Zwijnaarde 6
9052 Gent - Belgium
T +32 9 221 11 16
VAT BE0400.166.768 - R.P.R. Gent
info@compaktuna.be
www.compaktuna.be