COMPAKTUNA®

SEAL-ALL® CLEANER


Primer for silicone and adhesive sealants on smooth surfaces





CHARACTERISTICS

SEAL-ALL® CLEANER is a high-quality, fast-drying, ready-to-use colourless cleaner and primer in one product. Developed as an adhesion promoter for all types of sealants and adhesives on non-porous surfaces. Drying time 5 to 10 minutes. Cleans, degreases and improves adhesion in one treatment.



APPLICATIONS

Is used as a pre-treatment agent for various metal and alloy substrates, such as aluminium, steel, stainless steel, zinc, copper, lead, chrome and brass. Can also be used for surfaces provided with a powder coating and surfaces provided with a lacquer and/or paint system. We advise to test in advance whether the substrate will be affected. Is also a suitable pre-treatment agent for plastics such as ABS and PVC and for all other non-porous substrates.


Technical characteristics	Measured values
Base	Solvent
Density	0,76 g/ml
drying time	5-10 minutes
Flash point	+3 °C
Flammable	Yes

Mixing ratio		Packaging
Undiluted		500 ml/can
Colour		**Application temperature**
Colourless		+5 °C to +40 °C

SEAL-ALL® CLEANER

DIRECTIONS FOR USE


- The surface must be dry, clean, free of grease and dust.
- Do not use SEAL-ALL® CLEANER directly from the original packaging, but pour the product into a glass or can, using a quantity that can be used in 30 minutes.
- SEAL-ALL® CLEANER is applied evenly with a clean cloth in 1 movement. Replace dirty cloth and/or paper immediately.
- Do not apply sealant and/or glue until the drying time has elapsed (5 to 10 min.).
- For best results, apply sealant and/or adhesive within 6 hours of application.
- Avoid contact with treated surfaces, as this may adversely affect adhesion.





REMARKS

- Treated surfaces are unsuitable for applying paint, lacquer and/or coating systems. Only apply to areas where the adhesive and/or sealant is applied.
- When using SEAL-ALL® CLEANER, test in advance whether it will not affect the surface to be treated. (PMMA/PC can cause stress cracking)
- SEAL-ALL® CLEANER can sometimes cause reduced adhesion of tapes.



STORAGE TIME

Store in unopened original packaging, cool, dry and upright, between +5 °C and +25 °C. Shelf life: 12 months after production date.

20240920

As the applications of our products are diverse, no single application guideline can be laid down. All product data refl ect the state of knowledge of our products at the time of publication. Therefore all suggestions and recommendations concerning the use of our products are merely illustrative. Apply the product on a small and insignifi cant spot before starting to use our products to be sure the desired result is obtained. Always ask for the technical sheet of our products. Visit the website www.compaktuna.be. Consult our “technical department” which can be reached for free on the green number 0800/92279. The Dutch text shall be exclusively binding.
Version 10/02/2014. **COMPAKTUNA BV is EN ISO 9001 certified.**

COMPAKTUNA®
Quality & Innovation

A MEMBER OF HOLCIM GROUP

COMPAKTUNA bv/srl
Industriepark III
Industriepark Zwijnaarde 6
9052 Gent - Belgium
T +32 9 221 11 16
VAT BE0400.166.768 - R.P.R. Gent
info@compaktuna.be
www.compaktuna.be