

PLYWOOD DOOR-PAN



DESCRIPTION

Plywood Door-Pan, our specialised plywood panel for the door industry, is manufactured in standard door dimensions. It features a core made from 100% Eucalyptus hardwood and is bonded with melamine resin.

It is available in two versions: the standard version features high-quality, natural light-coloured face veneers, while the pre-primed version has an opaque white primer coating on one side.

APPLICATIONS

Suitable for use in humid environments and indoor industrial applications. Can be used for both structural and non-structural applications, depending on the panel thickness.

DIMENSIONS

2150 × 1220 mm			
Thickness (mm)	# / pack	# folds	Standard stock
18	50	11+2	x
22	43	13+2	

TECHNICAL SPECIFICATIONS

COMPOSITION

Core: 100% eucalyptus A-grade

Finish

- **Standaard:** high-quality natural light-coloured engineered face veneers
- **Pre-painted:** one side with high-quality white primer

SERVICE CLASS

EN636-2
CE2+ Structural + non-structural use (depending on thickness)

TOLERANCE

0,7 mm according EN315

BONDING

EN314-2/2 (melamine bonding)

DENSITY

± 580 kg/m³

REACH

Compliant

FIRE REACTION CLASS

D-s2,d0 (>=9mm)