Shades of Grey

TH-AYO-TS5101-B

Wood type | LDCwood® ThermoWood® ayous

> Durability class according to EN 350-1 : 1

Type of coating | STAIN, VARNISH

> Protection against mould and algae
> Protection against UV
> Intense pre-grayer
> Ideal for facades with different orientations or in combination with overhangs
> Semi-transparent
> Moisture-regulating
> Semi-film-forming

Brushed | yes

Colourfastness* | ++

Ease of maintenance** | +++

DIRT

Cleaning the wood

MOSS GROWTH

Clean using
medium-hard nylon brush and
power washer
+
rinse well

Let it dry

Apply stain, varnish

DEGRADATION OF WOOD AND/OR COLOUR

* An even transition from pre-greying to natural greying due to weathering.
** The frequency of implementation depends greatly on wood type, location and orientation.

A pre-greying treatment helps even out colour differences on the façade caused by sun and shade and requires no maintenance. It gradually fades as the wood naturally greys. As wood is a natural material with varying grain patterns and density, slight colour variations may occur.

Zuiddokweg 44
9000 Ghent
Belgium
+ 32 9 255 58 88
info@lemahieu.be

Vergunningenstraat 6
8400 Ostend
Belgium
+59 33 99 99
info@lemahieu.be

JenoWood
Zuiderkoggeweg 2a
1607 MV Hem
The Netherlands
+31 (0)228 72 26 61
info@jenowood.nl

LEMAHIEU GROUP

Version 1.2026

The disclaimer of Lemahieu Group applies to this sheet: www.lemahieu.be/en/disclaimer