

Shades of Grey

TH-SPR-TS5101-B



Wood type | LDCwood® ThermoWood® Spruce

> Durability class according to EN 350-1 : 2

Type of coating | STAIN, VARNISH

- > Protection against mould and algae
- > Protection against UV
- > Intense pre-grayer
- > Ideal for facades with different orientations or in combination with overhangs
- > Semi-transparent
- > Moisture-regulating
- > Semi-film-forming

Brushed | yes

Colourfastness* | ++

Ease of maintenance** | +++



Zuiddokweg 44
9000 Ghent
Belgium
+ 32 9 255 58 88
info@lemahieu.be

Vergunningenstraat 6
8400 Ostend
Belgium
+59 33 99 99
info@lemahieu.be

JenoWood
Zuiderkoggeweg 2a
1607 MV Hem
The Netherlands
+31 (0)228 72 26 61
info@jenowood.nl

* An even transition from pre-graying to natural greying due to weathering.

** The frequency of implementation depends greatly on wood type, location and orientation.

A pre-graying treatment helps even out colour differences on the façade caused by sun and shade and requires no maintenance. It gradually fades as the wood naturally greys. As wood is a natural material with varying grain patterns and density, slight colour variations may occur.



LEMAHIEU
GROUP